

AMENDMENTS TO THE CLAIMS:

Please cancel claims 1, 4, and 10-11 without prejudice or disclaimer and amend the claims as follows:

1. (Canceled)
2. (Currently Amended) A string type air damper comprising:
 - a cylinder formed in a tubular shape, defining a guide hole at one end portion thereof;
 - a piston, which moves in the cylinder;
 - a helical spring for biasing the piston toward the other end portion of the cylinder; and
 - a string member guided from inside of the cylinder to outside thereof through the guide hole, wherein:
 - the piston and the string member are integrally molded;
 - the string member branches into a plurality of portions and connects with the piston at a base end portion thereof; ~~and~~
 - the portions come together at a forward end portion of the string ~~member member~~;

and

the plurality of portions of the string member connect with different positions on the piston.
3. (Previously Presented) A string type air damper comprising:
 - a cylinder formed in a tubular shape, defining a guide hole at one end portion thereof;

Serial No.: 10/665,260
Docket No.: P21-155424M/MNN
NGB.286

a piston, which moves in the cylinder;
a helical spring for biasing the piston toward the other end portion of the cylinder; and
a string member guided from inside of the cylinder to outside thereof through the
guide hole, wherein:

the piston and the string member are integrally molded;
the string member has a flat belt shape;
the guide hole of the cylinder has a flat opening and a smooth arcuate face continuing
to a wide width edge of the opening; and
the string member having the belt shape is bent and guided along the arcuate face of
the guide hole.

4. (Canceled)

5. (Currently Amended) A string type air damper comprising:

a cylinder formed in a tubular shape;
a piston, which moves in the cylinder;
a helical spring for biasing the piston toward one end portion of the cylinder;
a guide cap attached to the other end portion of the cylinder and defining a guide hole;
and,
a string member guided from inside of the cylinder to outside thereof through the
guide hole, wherein:

the guide cap and the string member are integrally molded; and

Serial No.: 10/665,260
Docket No.: P21-155424M/MNN
NGB.286

the string member is hooked to the piston within the cylinder and is guided to the outside ~~thereof.~~ thereof;

the string member branches into a plurality of portions;

a base end portion of the string member is connected to the guide cap; and

the plurality of portions of the string member are connected to different positions on the guide cap.

6. (Currently Amended) The string type air damper according to claim 5, wherein:
- ~~the string member branches into a plurality of portions;~~
- ~~a base end portion of the string member is connected to the guide cap;~~
- the plurality of portions come together at a forward end portion of the string member;
- and
- the portions are hooked at the piston.

7. – 11. (Canceled)

12. (Previously Presented) The string type air damper according to claim 2, further comprising an end cap attached to the other end portion of the cylinder.

13. (Previously Presented) The string type air damper according to claim 2, further comprising a mount integrally formed on the piston for receiving an end portion of the helical compression spring.

Serial No.: 10/665,260
Docket No.: P21-155424M/MNN
NGB.286

14. (Previously Presented) The string type air damper according to claim 3, wherein the guide hole comprises a shape that substantially corresponds to a cross-section of the string member.

15. (Previously Presented) The string type air damper according to claim 3, further comprising a mount integrally molded on the piston for receiving an end portion of the helical compression spring.

16. (Previously Presented) The string type air damper according to claim 5, further comprising a mount integrally molded on the piston for receiving an end portion of the helical compression spring.

17. – 21. (Canceled)